

# SELLO-U HOMOGENEO - ESTILO HMU



N=BUNA-N  
V=FLUOROCARBONO

## INFORMACIÓN DEL SELLO

MATERIAL	80 A CAUCHO BUNA-N 90 A FLUOROCARBONO
RANGO DE TEMPERATURA	BUNA-N: -40° a +121°C FC: -29 a + 204°C
RANGO DE PRESIÓN	BUNA-N: 0 a 1,000 PSI FC: 0 a 2,000 PSI
NÚMERO DE PARTE	(Prefijo)(ST) - (DI) - (Altura)

SELLOS "U" PARA VÁSTAGO

N° de Parte	D.I.	D.E.	A.	Precio de Lista
<b>1/8" S/T</b>				
HMU12-0.62-15N	5/8	7/8	5/32	\$ 5.84
HMU12-0.62-15V	5/8	7/8	5/32	21.07
<b>5/32" S/T</b>				
HMU15-1.00-18N	1	1-5/16	3/16	\$ 5.58
HMU15-1.00-18V	1	1-5/16	3/16	10.71
HMU15-1.37-18N	1-3/8	1-11/16	3/16	7.46
HMU15-1.37-18V	1-3/8	1-11/16	3/16	22.15

N° de Parte	D.I.	D.E.	A.	Precio de Lista
<b>3/16" S/T</b>				
HMU18-1.75-21N	1-3/4	2-1/8	7/32	\$ 8.21
HMU18-1.75-21V	1-3/4	2-1/8	7/32	27.90
HMU18-2.00-21N	2	2-3/8	7/32	9.88
HMU18-2.00-21V	2	2-3/8	7/32	31.90
<b>7/32" S/T</b>				
HMU21-2.50-24N	2-1/2	2.93	.24	\$ 11.13
HMU21-2.50-24V	2-1/2	2.93	.24	37.51
HMU21-3.00-24N	3	3-7/16	.24	13.36
HMU21-3.00-24V	3	3-7/16	.24	45.01